



iTerra Elite II: System Specifications	
Maximum Plot Speed	6" per second (152.4 mm per second)
Print Technology	Single Pass 4 Color LED (CMYK)
Plotter Carriage Width	8.5" (215.9 mm)
Maximum Printable Width	8.24" (209.3 mm)
Print Resolution	300 dpi or 600 dpi
Consumables	Fanfold Paper, Toners, Drums, Fuser, and Transfer Belt
Sheet Sizes	Letter, Legal
Connectivity Interfaces	Centronics®, USB 2.0, 10/100 Network
Warranty	1 Year
Drivers	Windows XP, Vista & 7, 32 & 64 Bit
Options	Output Basket, Auto Stacker
Data Format (Internal)	PCL5C, PCL6
Dimensions (H X W X D)	17.1" x 21" x 26" (434.34 mm x 533.4 mm x 660.4 mm)
Power Requirements	110 - 127 VAC, 50/60 Hz @ 880W 220 - 240 VAC, 50/60 Hz @ 440W
Weight	Printer: 110 lbs (49.9 kg)
Operating Environment	Temperature: 10°C to 30°C (50 to 89.6°F) Humidity: 20 to 60% RH
Certifications	FCC Class A, CE *
<p>The Imaging Systems Group reserves the right to change product specifications without notice. Trademarks are the property of their respective manufacturers.</p> <p>© 2016 Copyright, The Imaging Systems Group Inc. All rights Reserved.</p> <p>* Has or will qualify for agency testing</p> <p>Centronics® is a Registered Trademark of Centronics Data Computer Corporation.</p>	