iTerra Mi875: System Specifications	
Maximum Plot Speed	6” per second (152.4 mm per second)
Print Technology	5 Channel Color Inkjet (CMYKK)
Plotter Carriage Width	8.75” (222.3 mm)
Maximum Printable Width	8.5” (215.9 mm)
Print Resolution	1600 dpi
Consumables	Fanfold Paper, Inks, Printheads, DI Wipe, Absorbant
Ink Cartridge Capacity	250 ml each
Connectivity Interfaces	USB 2.0, 10/100 Network
Warranty	1 Year
Drivers	Windows Vista, XP, 7, 8, 10 32 and 64 bit
Options	Front Input Tray, Media Output Catcher
Dimensions – Desktop (H X W X D)	17.44" x 21.17" x 10.67" (443 mm x 538 mm x 271 mm)
Dimensions – Rackmount (H X W X D)	19" x 22.36" x 10.37" (483 mm x 568 mm x 263 mm)
Power Requirements	100 - 127 VAC, 50/60 Hz @ 100W 220 - 240 VAC, 50/60 Hz @ 100W
Weight (Desktop)	60.55 lbs (27.47 kg)
Weight (Rackmount)	59.3 lbs (26.9 kg)
Operating Environment	Temperature: 15°C to 35°C (59 to 95°F) Humidity: 20 to 80% RH
Certifications	FCC Class A, CE, cTUVus*

The Imaging Systems Group reserves the right to change product specifications without notice. Trademarks are the property of their respective manufacturers.

© 2016 Copyright, The Imaging Systems Group Inc. All rights Reserved.

* Pending

911-28th Street NE Calgary, AB T2A 7X1 Canada Tel: 403.204.5200 Fax: 403.204.1971 Toll Free:1.866.415.iSys
www.isys-group.com