



V24: System Specifications

Maximum Plot Speed	2" per second (50.8 mm per second)
Print Technology	Direct Thermal
Plotter Carriage Width	24" (609.6 mm)
Maximum Printable Width	23.68" (601.47 mm)
Print Resolution	200 or 400 dpi
Maximum Bytes Per Scan	1184
Consumables	Roll Paper
Sheet Sizes	N/A
Connectivity Interfaces	Standard - Versatec™ Longline/Diff, Shortline/TTL Optional - Centronics®, 10/100 Network, USB
Warranty	6 Months
Drivers	Windows 2000, XP, Vista, 7, 8, 10 32 and 64 bit
Options	Pedestal, Media Catcher
Data Format	Raster
Dimensions – Desktop (H X W X D)	34" x 14.5" x 9.5" (863.6 mm x 368.3 mm x 241.3 mm)
Dimensions – Rackmount (H X W X D)	42" x 24" x 25" (1066.8 mm x 609.6 mm x 635 mm)
Power Requirements	110 VAC, 50/60 Hz, 515 Watts 240 VAC, 50/60 Hz, 515 Watts
Weight	Desktop: 76lbs (34.47kg) Rackmount: 105lbs (47.63kg)
Operating Environment	Temperature: 0°C to 35°C (32 to 95°F) Humidity: 5 to 95% RH
Certifications	FCC Class A, CE
<p>The Imaging Systems Group reserves the right to change product specifications without notice. Trademarks are the property of their respective manufacturers.</p> <p>© 2016 Copyright, The Imaging Systems Group Inc. All rights Reserved.</p> <p>Centronics® is a Registered Trademark of Centronics Data Computer Corporation.</p> <p>Versatec™ is a Trademark of Versatec Corporation.</p>	